

Harmsco® Band Clamp Filters

Harmsco® Band Clamp Filters utilize patented Up-Flow Filtration while simplifying installation and maintenance.

- ✓ All Housings constructed with 304 Stainless Steel**
- ✓ Available in either Electropolish (EP) or Polycoat (PC) finishes
- ✓ High Temperature Filters Available



BC4-1-T-EP
BC4-1-T-PC



BC4-2-T-EP
BC4-2-T-PC



BC4-3-T-EP
BC4-3-T-PC

Max flow rate (U.S. GPM)	Up to 25	Up to 50	Up to 75
Max flow rate (LPM)	Up to 95	Up to 190	Up to 285
Max. flow (M ³ HR)	Up to 5	Up to 12	Up to 17
Number of standard cartridges	4	8	12
Alternative cartridge	Single Only	Doubles	Triples
Pipe size	2" FPT	2" FPT	2" FPT
Drain	1/2" NPT	1/2" NPT	1/2" NPT
Filter height	19-1/2"	29-1/4"	39"
Floor space requirement	13" x 13"	13" x 13"	13" x 13"
Service height clearance	28"	47"	67"
Shipping weight	27 lbs.	32 lbs.	38 lbs.



BC6-1-T-EP
BC6-1-T-PC



BC6-2-T-EP
BC6-2-T-PC



BC6-3-T-EP
BC6-3-T-PC

Max flow rate (U.S. GPM)	Up to 42	Up to 84	Up to 126
Max flow rate (LPM)	Up to 159	Up to 318	Up to 477
Max. flow (M ³ HR)	Up to 10	Up to 19	Up to 29
Number of standard cartridges	6	12	18
Alternative cartridge	Single Only	Doubles	Triples
Pipe size	2" FPT	2" FPT	2" FPT
Drain	1/2" NPT	1/2" NPT	1/2" NPT
Filter height	26-1/2"	36-1/4"	46"
Floor space requirement	15" x 15"	15" x 15"	15" x 15"
Service height clearance	28"	47"	67"
Shipping weight	32 lbs.	37 lbs.	42 lbs.

***Poly Coat**

****T-316 Call for availability and quote**

Note: All units available in NPT or Victaulic Fittings

Harmsco recommends operation at 60-70% of maximum flow rate for optimum performance. Pressure rated to 150 psi (10 bar) max. Standard Harmsco® Up-Flow filter housings and filter cartridges rated for temperatures to 140°F (60°C); ratings based on pressure and time under load. All Stainless Filter housings and high temperature cartridges (see pages 9,11) recommended for temperatures to 250°F (121°C). Cartridges not included. For cartridge installation add \$55 service fee. Units also available with BSP threads as special order.

Note: All stainless steel housings are 304; 316 available upon request.