

Cartridges Listed Below

Harmsco® Hurricane® Filters with Single Hurricane® Cartridge

Combination cyclone separator and cartridge filter in a single compact design. Cartridge and filter sold separately.

Hurricane® filters are ideal for high solids and when a single “jumbo” cartridge is desired. Rated for temperatures to 140°F (60°C)* and pressures to 150 psi. Temperature ratings vary and depend on time under load. *Temperatures to 250°F (121°C) can be attained with optional SS Standpipe and Harmsco® high temperature cartridge installed (see Page 15).



Certified to ANSI-NSF 61



**HUR 40 HP
HUR 40 HPSS***

Up to 50
Up to 189
Up to 12
2"
1"
21"/54 cm
15" x 15"
31"/79 cm
40 lbs. / 18 kg
14"x16"x21"



**HUR 90 HP
HUR 90 HPSS***

Up to 100
Up to 378
Up to 24
2"
1"
31"/79 cm
15 x 15"
51"/130 cm
51 lbs. / 23 kg
14"x16"x38"



**HUR 170 HP
HUR 170 HPSS***

Up to 150
Up to 568
Up to 36
2"
1"
41"/105 cm
15" x 15"
72"/183 cm
64 lbs. / 29 kg
14"x16"x42"

Max flow rate (U.S. GPM)
Max rate (LPM)
Max rate (M³HR)
Pipe size (NPT)
Drain (NPT)
Filter height
Floor space requirement
Service height requirements
Shipping weight
Carton dimensions

*Stainless steel standpipe for high temperature available.

Note: Harmsco recommends operation at 60-70% of maximum flow rate for optimum performance. All stainless steel housings are 304; 316 available upon request.

Harmsco® Hurricane® and WaterBetter® Replacement Cartridges

Made of pleated polyester filter media for long life and high dirt holding capacity; rated for temperatures to 140°F (60°C) packaged one per carton; cleanable and reusable in most applications. Shipping weights: Model 40 cartridges 4 lbs.; Model 90 cartridges 7 lbs.; Model 170 cartridges 10 lbs. Carton dimensions: HC-40 is 9"x9"x11"; HC-90 is 9"x9"x21"; HC-170 is 9"x9"x32". Hurricane® cartridges rated for pressures to 50 psid.



Certified to ANSI-NSF 61

Cartridges for Model HUR 40 HP

Product Code	Micron
HC/40-0.35	0.35
HC/40-1	1
HC/40-5	5
HC/40-10	10
HC/40-20	20
HC/40-50	50
HC/40-100	100
HC/40-150	150
HC/40-EZ-CLEAN*	N.R.

Cartridges for Model HUR 90 HP

Product Code	Micron
HC/90-0.35	0.35
HC/90-1	1
HC/90-5	5
HC/90-10	10
HC/90-20	20
HC/90-50	50
HC/90-100	100
HC/90-150	150
HC/90-EZ-CLEAN*	N.R.

Cartridges for Model HUR 170 HP

Product Code	Micron
HC/170-0.35	0.35
HC/170-1	1
HC/170-5	5
HC/170-10	10
HC/170-20	20
HC/170-50	50
HC/170-100	100
HC/170-150	150
HC/170-EZ-CLEAN*	N.R.
HC/170-PM**	N.R.

*100% Synthetic media to prefilter organic matter and particulate. **Poly Mesh. Note: High temperature cartridges available; see Page 15.

Activated Carbon Cartridges for Hurricane® and WaterBetter® Filter Housings

With outer wrap of pleated five micron polyester media to extend filter life.

Activated carbon cartridges for Hurricane® filter housings for taste, odor and chlorine removal. High carbon content for extended throughput. Outer wrap of pleated five micron Polyester-Plus™ filter media to protect the carbon by removing sediment and extend filter life. Not recommended in drinking water applications where water is not micro-biologically safe.

Product code	Carbon content (lbs.)**	Capacity (gals.)**	Chlorine reduction*
HC/40-AC-5	3 (min.)	33,000	90%-95% at 5 GPM
HC/90-AC-5	6.25 (min.)	66,000	90%-95% at 10 GPM
HC/170-AC-5	10 (min.)	100,000	90%-95% at 15 GPM

*Results may vary and are based on flow and other factors. **Approx.



Hurricane® A/C cartridge

For The Above Housings