



Filtration Systems by Harmsco® Using Hurricane Filters

Skid mounted filtration systems are available to reduce labor and installation costs. All systems include steel skids assembled with shut-off valves, check valves and pressure gauges. Controls for pumps are included when pump systems are ordered. Please see our Systems Brochure for full details.

OPTIONS:

- NEMA enclosure for pump systems in outdoor installations
- Filter service beacon
- Automatic purge valve for high solids application
- Crating for export

Shut-off and check valves installed to allow each individual filter to be isolated for servicing on all parallel systems. Filter Service Beacons and Automatic Purge Valves (if ordered) are tied in with all filters in parallel installations and with first filter only in series installations. Nema 12 enclosure with 10V control standard for indoor installation. 110 vac/15 amp plug for beacon included if pump is not ordered.

STANDARD MODELS

Model No. With Pump	Pump Size	Rated Flow (approx.)		Model No. Without Pump	Number of HUR170-HP Filters	Inlet/ Outlet
		GPM	LPM			
Parallel Installation Filters						
PFS-1-P	5 HP	100	378	PFS-1	1	2" NPT
PFS-2-P	7.5 HP	200	757	PFS-2	2	3" FLG
PFS-3-P	15 HP	300	1,135	PFS-3	3	4" FLG
PFS-4-P	20 HP	400	1,514	PFS-4	4	4" FLG

CUSTOM PRODUCT SOLUTIONS AVAILABLE!
PLEASE CALL FOR YOUR SPECIFICATION REQUEST FORM.

COMING SOON

New Non-Cellulose Cartridges

In early 2007, Harmsco will begin offering a new line of filter cartridges that will incorporate a Synthetic Composite Media. The Newly Engineered Media contains no binders or cellulose and has been developed specifically for drinking water applications.

Initially, the new cartridges will be offered in 1, 5 and 20 micron nominal ratings, with other ratings under development.

Watch Harmsco.com for the release of this new product line.